LED Dome lights & Signal Lights - Model 412

PRODUCT INFORMATION

Description 12-48V Clear LED Dome Light with 7"

Bare Leads, No Switch, No Timer

Height 57.15 mm / 2.25 in Width 165.10 mm / 6.5 in Depth 27.69 mm / 1.09 in

Shape Rectangular Polycarbonate **Outer Lens Material**

Outer Lens Color Clear

Polycarbonate **Housing Material**

Housing Color Black

Mounting Hardware (x2) M4-0.7 x 16 Mounting Bolts

Description

Mounting Type Low Profile Mount **Minimum Operating** -40 °C / -40 °F

Temperature


Maximum Operating 65 °C / 149 °F

Temperature

Connector or Wiring 7" Bare Leads **Product Weight** 0.33 lbs / 0.15 kgs **Shipping Weight** 5.06 lbs / 2.3 kgs



PRODUCT DIMENSIONS



Print date: 2025-04-24

LED Dome lights & Signal Lights - Model 412

ELECTRICAL SPECIFICATIONS

Input Voltage12-48V DCRed WirePositiveBlack WireNegative

Current Draw 0.10A to 0.13A @ 12V DC

0.055A to 0.08A @ 24V DC 0.045A to 0.07A @ 36V DC 0.045A to 0.07A @ 48V DC

REGULATORY STANDARDS COMPLIANCE









Buy America Standards Eco Friendly IEC IP67 SAE J1113-13

UL Recognized

PHOTOMETRIC SPECIFICATIONS

Nominal LED Color 5000 K

Temperature

Beam Pattern(s) Interior - Dome Light



LED Dome lights & Signal Lights - Model 412

APPLICATIONS























PRODUCT WARNINGS

For California residents:

▲ WARNING: Cancer and reproductive harm - www.P65Warnings.ca.gov.

▲ AVERTISSEMENT: Cancer et effet nocif sur la reproduction - www.P65Warnings.ca.gov.

RELATED PRODUCTS







0443011 12-48V Clear LED Dome Light with 7" Bare Leads & Switch, No Timer

Part Number



0443301 12-48V Clear LED Dome Light with Deutsch Connector, Switch & 60 Minute Timer

Part Number