LED Work Light - Model 785

PRODUCT INFORMATION

Description 12V LED Work Light with Trapezoid

Beam Pattern

 Height
 82.00 mm / 3.23 in

 Width
 124.00 mm / 4.88 in

 Depth
 62.00 mm / 2.44 in

Shape Rectangular
Outer Lens Material Polycarbonate

Outer Lens ColorClearHousing MaterialNylon 66Housing ColorBlack

Minimum Operating $-40 \, ^{\circ}\text{C} \, / \, -40 \, ^{\circ}\text{F}$

Temperature

Maximum Operating 65 °C / 149 °F

Temperature

Connector or Wiring Integral connector


Mating Connector PE 12124819, or PE 12020599


Product Weight 0.33 lbs / 0.15 kgs **Shipping Weight** 0.56 lbs / 0.25 kgs

Additional Information Wire inputs are not polarity dependant.



PRODUCT DIMENSIONS









LED Work Light - Model 785

ELECTRICAL SPECIFICATIONS

Input Voltage12V DCOperating Voltage9-16V DC

Transient Spike Protection 150V Peak @ 1 HZ-100 Pulses

Current Draw 1.2A @ 12V DC

REGULATORY STANDARDS COMPLIANCE









Buy America Standards Eco Friendly IEC IP67 IEC IP69K

PHOTOMETRIC SPECIFICATIONS

Raw Lumen Output 1,242 Effective Lumen 460

Output

Candela Output 1,380 **Nominal LED Color** 5000 K


Temperature

Beam Pattern(s) Forward Lighting - Trapezoid

10+ Lux

1 Lux

0.25 Lux



APPLICATIONS







Print date: 2024-12-12



LED Work Light - Model 785

INSTALLATION & APPLICATION INFORMATION

The Model785 work light fits Case Skid Steers, for 12V DC systems:

- SR (wheel radial lift)
- SV (wheel vertical lift)
- TR (track radial lift)
- TV (track vertical lift)

PRODUCT WARNINGS

For California residents:

▲ WARNING: Cancer and reproductive harm - www.P65Warnings.ca.gov.

▲ AVERTISSEMENT: Cancer et effet nocif sur la reproduction - www.P65Warnings.ca.gov.

RELATED PRODUCTS



Part Number 0554213 12V LED Work Light with Trapezoid Beam Pattern - 2 Light Kit

